MODULE 2- VERSION "C"

JSEA, HAZCOM, INCIDENT PREVENTION SIGNS & TAGS, PPE & FALL PROTECTION

Do not write on this test question sheet. Circle the letter on the test answer that corresponds to the correct answer. When test is complete, return this test and your answer sheet to your instructor to grade.

- 1. Safety-toed boots are required to be worn when?
 - A. Shop
 - B. Yard
 - C. Field locations
 - D. All of the above
 - E. B & C only
- 2. Global Harmonization System (GHS) is the new international approach to hazard communication. It is the foundation for:
 - A. Safe use of chemicals
 - B. Risk Management systems
 - C. Hazard communication
 - D. All of the above
- 3. What of the following is NOT a responsibility of the employee regarding PPE use?
 - A. Don and use correctly
 - B. Care for PPE
 - C. Design factors
 - D. Know the limitations
- 4. There are two main categories of respirators:
 - A. Air purifying & air filtering
 - B. Air supplied & self-contained
 - C. Air purifying, air filtering, & self-contained
 - D. Air supplied & air purifying
 - E. All of the above
- 5. Safety glasses & face shields must be worn when doing which of the following jobs?
 - A. Power washing
 - B. Grinding
 - C. Functions that produce flying debris
 - D. All of the above
- 6. While working at heights, what would be some conventional safety systems used?
 - A. Guardrail systems
 - B. Personal fall protection
 - C. Ladders
 - D. A & B only

Module 2 Version C Revised: May 2015

- 7. When is the best time to perform a JSA?
 - A. After the accident
 - B. After the work shift
 - C. Before beginning any new work
 - D. Only when the boss is there
- 8. What is the OSHA required height for fall protection in general industry?
 - A. 4 feet
 - B. 6 feet
 - C. No requirement
 - D. None of the above
- 9. Which of the following is NOT a control measures?
 - A. Engineering controls
 - B. Administrative controls
 - C. Supervisor controls
 - D. PPE
- 10. To avoid "caught by" hazards, employees should:
 - A. Cut their hair short
 - B. Tie up long hair and secure it under a hard hat
 - C. Never wear rings, watches, other jewelry
 - D. Both B & C
 - E. All of the above
- 11. What other safety precaution must be in effect before the use of PPE?
 - A. Elimination/Substitution
 - B. Engineering Controls
 - C. Administrative Controls
 - D. All of the above
- 12. Employees working in areas where the noise level exceeds 85 decibels are required to wear hearing protection.
 - A. True
 - B. False
- 13. A properly fitted body harness must:
 - A. Be snug to the body
 - B. Only have room for two fingers between the leg & leg straps
 - C. Both A & B
 - D. None of the above
- 14. Chemical warning labels must be legible and:
 - A. Written in the language of origin
 - B. Written in English
 - C. Written in any common language

Module 2 Version C Revised: May 2015

- 15. 80% of all errors with fall protection systems involves the anchor point
 - A. True
 - B. False
- 16. The wording of signs and tags should:
 - A. Easy to read and concise
 - B. Make a positive suggestion
 - C. Contain sufficient information to be understood
 - D. All of the above
- 17. There are two basic types of chemical hazards the regulation applies to:
 - A. Health and Physical
 - B. Mental and chemical
 - C. Psychological and Physical
- 18. Good communication is critical to avoid accidents during simultaneous operations.
 - A. True
 - B. False
- 19. Hazard Communication is also known as the "Right to Know" standard
 - A. True
 - B. False
- 20. Employees have to do what in order to wear a respirator?
 - A. Answer a medical questionnaire
 - B. Be fit tested (Type specific)
 - C. Be trained on use
 - D. All of the above

Module 2 Version C Revised: May 2015